

Gas measurement technology

Hand-held measurement device

Digital manometer **DruckTest 2000**

Gas leak detector **VibraGAS** and combination device

LeckOmiO - Leak location with intelligent options



INSYNRID

Official Distributor of



www.esders.com



- Rugged hand-held instruments with ergonomic aluminum housing
- Wide range of applications in the gas installation
- Load- and tightness tests according to TRGI
- Powerful gas detector with vibration alarm and digital display reading for gas leak detection
- High contrast LCD display with backlight for an optimal presentation of all measured values
- Easy replacement of batteries with innovative battery Management
- Systematic evaluation of the measured data using Esders PC-1 software
- Graphical printout on site on mobile printer
- Simple operation with intuitive menu navigation
- Practical accessories for all applications



Technical data	
Display	LCD graphic display with 128 x 64 pixels + special characters, with backlight
Power supply	4 pcs 1.5V Alkaline AA Batteries or NiMH battery pack
Operating time	with alkaline manganese batteries > 100 h at pressure measurement (without lighting) > 20 hours at Gas detection (without lighting)
Measuring range	0 bis 10.000 ppm Methan; Auflösung 1, 10, 50, 100 und 1.000 ppm 0 bis 200 mbar (hPa) und 200 bis 2000 mbar; Auflösung 0,1 mbar und 1 mbar
Operating Temperature	- 20°C to + 50°C
dimensions	149-165 x 58 x 34 mm without gooseneck microphone (gooseneck 162 mm)
weight	400 g with batteries

www.insynrid.com

Hand held measurement instruments

Typical applications are:

Load and tightness testing according to TRGI, regulator examination, measurement of flow, resting and working pressures, pressure tests on gas pipes and gas pipes free examination of their external leaks.

The instruments are available as single or combination device and therefore versatile in the gas installation. Through the intuitive Esders operating philosophy a simple and economical operation is given.

The following menu options are available:

- **Pressure Test** display of starting pressure, final pressure, measurement time and pressure drop, as well as minimally and maximum pressure value.
- **Regulator Test** display of the outgoing pressure, closing pressure, safety pressure release valve response pressure and leak-proof completion, upper and lower deactivation of safety shut-off valve and leak-proof completion.
- **Load test according to TRGI** Menu-driven procedure with individual Adjusting of the measuring time to the requirements of the TRGI load testing
- **Tightness test according to TRGI** Menu-driven procedure with individual Adjusting of the measuring time to the requirements of the TRGI tightness testing
- **Building inspection** detection of smallest leaks in plumbing lines and connections. In addition to the optical and acoustic signal a vibration alarm is available.
- **Settings** Custom configuration of the operating parameters such as the measuring unit, automatic switch off or the duty cycle of the backlight to the user's requirements.
- **Adjustment** Sensor sensitivity test and calibration of the device according to DVGW Note G 465-4 by applying test gas and set point adjustment by pressing a button

Function	VibraGAS	DruckTest 2000	LeckOmi0
Building Inspection	●		●
Pressure Test		●	●
Regulator Test		●	●
Load test according to TRGI		●	●
Tightness test according to TRGI		●	●

Accessories



Item no. 212011
Handpump



Item no. 212013
Adapter pressure



Item no. 292004
Burner test



Item no. 312018
Test cap DN 25



Item no. 262009
Printer



Item no. 262008
Carrying Case

Further accessories on request!



Item no. 202002
Power supply
230/12 V DC



Item no. 262003
Docking station for
HMG



Item no. 262023
Leather protective bag



Item no. 262002
Strap for Handheld
Instruments

Subject to technical modifications! Status 09/2016



INSYNRID